

Cassette Laser Marker	
Dimensions	10.75" W x 15.75" D x 14" H - 25" H with magazine (273mm W x 400mm D x 356mm H - 635mm H with magazine)
Weight	43 lbs (19.5 kg)
Laser	Class 1 Sealed Laser, 5W output
Electrical requirements	100 – 240V, 50/60Hz, 3A - The main power supply voltage fluctuations should not exceed + or - 10%.
Electrical output to filter unit	Voltage and frequency are identical to what is supplied to the Cassette Marker. The maximum current to be drawn from the outlet is 1A
Cassette Capacity	1 magazine, capable of holding up to 70 cassettes
Cassette compatibility	Only compatible with Doped Cassettes
Speed	5 seconds cassette to cassette
Resolution	200 lines per inch
Barcode compatibility	Code 128, Code 39, DataMatrix, PDF417
Connectivity to PC	USB / Ethernet / Serial
Filter Unit GD125	
Dimensions	13 3/16" W x 13 3/16" D x 20 1/16" H (335mm W x 335mm D x 510mm H)
Weight	35 lbs. (16 kg)
Voltage Range/Power	100-240 VAC, 50/60Hz/100W
Sound Level at 1 m	50db (A)
Electrical requirements	Filter unit is powered directly by the Cassette Marker
Filter compatibility	Only use replacement filters specifically designed for the filter unit. Compatible filters can be ordered directly through InfoSight.

